

PCT


WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 7 : E04D 12/00		(11) International Publication Number: WO 00/37751
A1		(43) International Publication Date: 29 June 2000 (29.06.00)
(21) International Application Number: PCT/DK99/00724		(81) Designated States: AE, AL, AM, AT, AT (Utility model), AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, CZ (Utility model), DE, DE (Utility model), DK, DK (Utility model), DM, EE, EE (Utility model), ES, FI, FI (Utility model), GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KR (Utility model), KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SK (Utility model), SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).
(22) International Filing Date: 21 December 1999 (21.12.99)		
(30) Priority Data: PA 1998 01698 21 December 1998 (21.12.98) DK		
(71) Applicant (for all designated States except US): ICOPAL A/S [DK/DK]; Amager Landevej 233, DK-2770 Kastrup (DK).		
(72) Inventor; and (75) Inventor/Applicant (for US only): HARDER, Sven [DK/DK]; Bybakken 6, DK-2625 Vallensbæk (DK).		
(74) Agent: PLOUGMANN, VINGTOFT & PARTNERS A/S; Sankt Annæ Plads 11, P.O. Box 3007, DK-1021 Copenhagen K (DK).		Published With international search report.

(54) Title: A WATER VAPOUR BARRIER AND A METHOD OF MAKING THE SAME



(57) Abstract

The present invention relates to a water vapour barrier (15) that comprises a first, water impervious membrane (19) having a plurality of first through openings (21) defined therein, and a second, water impervious membrane (22) which is arranged opposite to the first membrane (19). A water absorbing material (18) is arranged within one or more spaces defined between the first and second membranes (19, 22), and the water vapour barrier (15) is characterised in that at least part of the second membrane (22) is of a material of the type having a water vapour diffusion resistance, which varies in dependency of the relative humidity of air in contact therewith, such that the vapour diffusion resistance is reduced when the relative humidity increases, and vice versa. The invention further relates to a method of making the water vapour barrier.